

Ford Batten Light (Zigbee)

SMI7040

This product must be installed by a licensed electrician



Features

- Zigbee 3.0 compliant
- Controllable colour temperature (CCT) via the app (3000K 5700K)
- On/off & dimming control via the app
- Customizable timers & schedules via the app
- Works with both Amazon Alexa and Google Assistant
- 3 year in-home warranty



Network/Device Requirements

Connectivity	Zigbee
Requirements	Mercator Ikuü zigbee hub
Protocol	IEEE 802.15.4
Wireless Frequency	2.4GHz
App Requirements	Mobile device running iOS or Android.
	(Refer to ikuu.com.au for minimum specs)

Included Accessories


Mounting screws

Technical Specifications

Standby Wattage <0.05W Max Load 40W IP Rating IP20 (indoor use only) Colour White Housing Material Polycarbonate & coated steel Weight 1.8kg Dimensions 1235mm x 77mm x 73mm Lumens 4000lm Colour Range (CCT) Adjustable, 3000K to 5700K CRI >80 Ream Angle 130°	Supply Voltage	220 - 240V a.c. 50Hz
IP Rating IP20 (indoor use only) Colour White Housing Material Polycarbonate & coated steel Weight 1.8kg Dimensions 1235mm x 77mm x 73mm Lumens 4000lm Colour Range (CCT) Adjustable, 3000K to 5700K CRI >80	Standby Wattage	<0.05W
Colour White Housing Material Polycarbonate & coated steel Weight 1.8kg Dimensions 1235mm x 77mm x 73mm Lumens 4000lm Colour Range (CCT) Adjustable, 3000K to 5700K CRI >80	Max Load	40W
Housing Material Polycarbonate & coated steel Weight 1.8kg Dimensions 1235mm x 77mm x 73mm Lumens 4000lm Colour Range (CCT) Adjustable, 3000K to 5700K CRI >80	IP Rating	IP20 (indoor use only)
Weight 1.8kg Dimensions 1235mm x 77mm x 73mm Lumens 4000lm Colour Range (CCT) Adjustable, 3000K to 5700K CRI >80	Colour	White
Dimensions1235mm x 77mm x 73mmLumens4000lmColour Range (CCT)Adjustable, 3000K to 5700KCRI>80	Housing Material	Polycarbonate & coated steel
Lumens 4000lm Colour Range (CCT) Adjustable, 3000K to 5700K CRI >80	Weight	1.8kg
Colour Range (CCT) Adjustable, 3000K to 5700K CRI >80	Dimensions	1235mm x 77mm x 73mm
CRI >80	Lumens	4000lm
	Colour Range (CCT)	Adjustable, 3000K to 5700K
Beam Angle 130°	CRI	>80
Dealt Alight 130	Beam Angle	130°
Dimmable Via the app (1)	Dimmable	Via the app ⁽¹⁾
Compliance / AS/NZS 60598.2.1, AS/NZS 60598.1,	Compliance /	AS/NZS 60598.2.1, AS/NZS 60598.1,
Standards AS/NZS 4268, CISPR 15 & CISPR 32	Standards	AS/NZS 4268, CISPR 15 & CISPR 32

 $^{^{\}mbox{\tiny (1)}}\mbox{This}$ luminaire is app dimmable only and must not be used in conjunction with other dimmers

Dimensions







This product is valid for 3 years in-home warranty from the date of purchase. Please retain proof of purchase and certificate of compliance from the installation to make a claim. Please visit https://www.mercator.com.au/product-support/warranty for more information. For Mercator Ikuü contractor or end consumer support please visit www.ikuu.com.au or contact our customer service team on 1300 552 255 or via email at customercate@mercator.com.au







