


Walter Downlights (Wi-Fi)

SMD4106W / SMD4106W-RGB SMD4109W / SMD4109W-RGB



Features

- Wi-Fi (No hub required)
- Fitted with 1.9m cord and plug
- Recessed lens
- IC-4 and IP44 below ceiling
- Available in 70mm and 92mm cut outs
- Available in either:
 - Controllable colour temperature (CCT) via the app (3000K-5700K)
 - RGB + Controllable colour temperature (CCT) via the app (3000K-5700K)
- On/off & dimming control via the app
- Customizable timers & schedules via the app
- Works with both Amazon Alexa and Google Assistant



Connectivity	Wi-Fi
Requirements	Existing 2.4GHz Wi-Fi network
Protocol	IEEE 802.11 b/g/n
Wireless Frequency	2.4GHz
App Requirements	Mobile device running iOS or Android. (Refer to ikuu.com.au for minimum specs)

Technical Specifications

	SMD4106W	SMD4106W-RGB	SMD4109W	SMD4109W-RGB	
Cut-out Size (Ø)	70mm		92mm		
Max Load	7W		9W		
Supply Voltage	220 - 240V a.c. 50Hz				
Standby Wattage	<1W				
IP Rating	IP44 below ceiling				
Lead Length	1.9m				
Housing Colour	White				
Housing Material	Aluminium				
Weight	240g		260g		
Dimensions (H x Diam)	23mm x 90mm (total)		25mm x 110mm (total)		
Lumens	570lm		740lm		
Colour Range (CCT)	Adjustable, 3000K to 5700K				
RGB	No	Yes	No	Yes	
CRI	>80				
Beam Angle	110°				
Dimmable	Via the app ⁽¹⁾				
Estimated Lifetime	30,000 hours				
Compliance /	AS/NZS 61347.1, AS/NZS 61347.2.13, AS/NZS 60598.2.2, AS/NZS 60598.1, AS/NZS 4268,				
Standards	CISPR 15, CISPR 32				

⁽¹⁾ This luminaire is app dimmable only and must not be used in conjunction with other dimmers



This product is valid for 3 years warranty from the date of purchase. Please retain proof of purchase and contact our customer service team to make a claim. Please visit https://www.mercator.com.au/product-support/warranty for more information. For Mercator Ikuü contractor or end consumer support please visit www.ikuu.com.au or contact our customer service team on 1300 552 255 or via email at customercate@mercator.com.au







